

Debut 2.0™ Series by Andrew Jones.

Everything we do is different.

Few speakers have garnered such critical acclaim as the original Debut Series by ELAC. They established a new value proposition, with build quality and performance never before attainable at such an affordable price. Debut “changed the game,” and has now has changed it again with the Debut 2.0 Series—proof that ELAC can’t leave well enough alone. Redesigned from the ground up, these speakers sound even more remarkable than the ones that sparked the revolution in affordable high-end sound.



Debut F6.2 Aramid-Fiber Floorstanding Speaker

It takes Debut 2.0 to the limit.

The pinnacle of ELAC’s Debut 2.0 Series is the F6.2, a floorstander with credentials to play in the big leagues. Whether your aim is to build a formidable two-channel or surround-sound system for music and home theater, there isn’t a more capable performer for anywhere near the price. It’s a “no-excuses” speaker guaranteed to change your definition of value in high-end audio.

DEBUT 2.0 SERIES FEATURES

All-New Design—All-New Debut!

Everything about Debut 2.0 has been improved, including completely redesigned custom drivers that deliver greater accuracy, and robust cabinets for even higher resolution and freedom from resonances.

New Tweeter with Wide-Dispersion Waveguide

A new silk-dome tweeter features a wide-roll surround and takes response up to 35,000 Hz for even more lifelike high frequencies. The waveguide improves directivity control and eliminates the diffraction modes inherent in traditional box enclosures.

New Woven Aramid-Fiber Woofers

The revised shape of the aramid cones offers even greater stiffness and damping, far superior to polypropylene or paper. The added strength allows

more flexibility in design to achieve a smoother, extended low-frequency response.

New, Larger Cabinets

Thick MDF cabinets with a luxurious textured vinyl finish are larger, and incorporate specially designed internal bracing to add stiffness and strength. This bracing greatly reduces cabinet vibrations that cause unwanted coloration to the sound. Because the only parts of a speaker that should be moving are the speaker drivers themselves.



F6.2 SPECIFICATIONS

SPEAKER TYPE	3-way, bass reflex
FREQUENCY RESPONSE	39 to 35,000 Hz
NOMINAL IMPEDANCE	6 Ω
SENSITIVITY	87 dB at 2.83 v/1m
CROSSOVER FREQUENCIES	90 Hz / 2,200 Hz
MAXIMUM POWER INPUT	140 Watts
TWEETER	1-inch cloth dome
WOOFER	3 x 6.5-inch woven aramid-fiber cones with oversized magnet and vented pole piece
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
PORTS	3 x dual flared
BINDING POSTS	5-way metal
WIDTH	7.69 in / 195 mm
HEIGHT	43.18 in / 1097 mm
DEPTH	10.55 in / 268 mm
WEIGHT	43.9 lb / 19.9 kg

